



Specification Sheet

800T Tuff 7.0 mil Tag

Features:

- Thermal transfer, V-Max® polyolefin 7.0 mil tag
- Some smear/scratch resistance
- Good durability and chemical resistance
- Available in white (05025RM)

Suggested Applications:

- Nursery tags
- Lumber tags
- Outdoor storage tags
- Water-immersed tags

Material Construction:

	Description	Caliper
Facestock	Opaque white polyolefin	7.0 mil
	Total	7.0 mil

Temperature Performance:

- Minimum Application Temperature: N/A
- Service Temperature: -70° F to 200° F (-57° C to 93° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: 2 years





Specification Sheet **800T Tuff 7.0 mil Tag**

Suggested Ribbons for Applications with Chemicals

Ribbon	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
5095	X	X	X	X	X	X			X								

X indicates acceptable chemical resistance

V-Max is a registered trademark of Van Leer Flexibles, Inc.

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

